

AFFINITY 4 BIRTHING BED

HELPING TO DELIVER SAFETY

Designed to help deliver a safe and comfortable maternal environment.

HELPING TO DELIVER COMFORT

Keeping mom comfortable throughout the birthing experience should be paramount.

HELPING TO DELIVER CONVENIENCE

Designed to help facilitate smooth and efficient patient care.

MAXIMUM PATIENT WEIGHT

500lb bed weight limit. 400lb foot section weight limit.

PATIENT TRANSPORT



GAS ASSIST BED TILT

The bed can achieve 8° of trend-like positioning and can be activated as needed in an emergency situation.

15° PELVIC TILT

Pelvic tilt designed to provide patient with support and comfort.



PATIENT TRANSFER

Zero-transfer gap for a seamless transfer of your patient.

MATTRESS OPTIONS

The cut of the mattress is designed to provide space which allows perineal access



"DUAL-LOCKING" CASTERS

Two points of contact designed to provide stability by helping with rolling or swiveling

BRAKE AND STEER PEDALS

Large surface with gripping pads



Customize patient comfort with the push of a button.

BATTERY BACKUP

Enables function of the bed during transport or loss of power.



STOW & GO FOOT SECTION

Exclusive, ergonomic design; foot section slides and stores under the bed.

LIGHT-WEIGHT FOOT SECTION

Handles and angular stand to keep mattress off the floor.



WIDE SLEEP DECK

35" surface width gives mom room in bed.

POSITIONING CALF SUPPORTS

Adjustable calf supports ergonomically designed to help support optimal positioning during delivery.





AFFINITY 4 BIRTHING BED

TECHNICAL SPECIFICATIONS

	Product Number	P3700
	Full Bed Length	90" (229 cm) P3700A-P3700C 92" (234 cm) P3700D-P3700E
	Bed Width Siderails Up Siderails Down	39" (99 cm) 36" (91 cm)
	Bed Height Low (with mattress) High (with mattress) Maximum Height of Seat Section in Trend-like Position	24" (61 cm) 39" (99 cm) 40" (102 cm)
	Mattress Length Width Thickness (head section) Thickness (foot section)	78" (198 cm) 35" (89 cm) 5" (12.7 cm) 3.5" (8.9 cm)
	Critical Angles Maximum Head Elevation Maximum Seat Elevation Maximum Trend-like Positioning	63° 15° 8°
	Maximum Lift Canacity	

Maximum Lift Capacity

 Bed
 500 lbs [227 kg]

 Foot Section
 400 lbs [181 kg]

Caster Size 5" (12.7 cm) standard on bed /

6" (15 cm) option available

Bed Weight 480 lbs (218 kg)



STANDARD FEATURES

V-Cut or Straight Cut Surfaces Removable Foot Section Battery Backup Powered Foot Section Four Wheel Dual-locking Casters OneStep Siderail Release Plastic Blow-Molded Head Panel Automatic Nightlight Lock-out Controls Manual Trend-like Positioning Instant CPR Tuck away Labor Grips Automatic Seat Tilt (15°) Siderail Controls IV Pole Plastic Blow Molded Head Panel Hinged Foot Section Mattress Central Brake and Steer Fluid Basin

OPTIONAL FEATURES

Prevention Surface
Air package for lumbar and seat support
Nurse Call, Lighting, Entertainment & UTV
Contemporary Headboard
Calf Supports
Push Handles

ACCESSORIES

Universal Instrument Tray Labor Bar Drainage Bag Hook Kit Permanent IV Pole Line Managers Foot Rest Bar (for lift off beds) Full Leg Supports Full Leg Supports, Telescoping Drapes - Medline/Proxima Oxygen Tank Holder

For more information, contact your Baxter Sales Representative,

call us at 1-800-422-9837 or email us at cfs customer service@baxter.com.

Baxter.com

Baxter International Inc.
One Baxter Parkway / Deerfield, Illinois 60015
Baxter, Affinity, OneStep and Stow & Go are trademarks of Baxter
US-CS133-220001 [v3.0] 09/2024

Dovozce/Distributor ZP pro ČR:



DARTIN spol. s r.o. Suchdolská 688, 252 62 Horoměřice Tel./fax: 241 470 361, 261 216 076 www.dartin.cz info@dartin.cz Dovozca/Distribútor ZP pre SR:



L. Podjavorinskej 25, 080 05 Prešov Tel./fax: 051/773 4403, 772 3634 www.dartin.sk info@dartin.sk